



Surrounding You with Exceptional Protection

# SAFETY DATA SHEET

Issue Date 01-Aug-2016

Revision Date 03-Apr-2023

Version 2

## 1. IDENTIFICATION

### Product identifier

**Product Name** TL-220-S HT

### Other means of identification

**Product Code** 436B5

**UN/ID no** UN1263

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Industrial Coatings

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

BLOME INTERNATIONAL

1450 Hoff Industrial Drive

O'Fallon, MO 63366

#### **Emergency telephone number**

**Company Phone Number** 636-379-9119

**Emergency Telephone** CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 1
Flammable liquids	Category 3

### Label elements

#### **Emergency Overview**

#### **Danger**

#### **Hazard statements**

Harmful if swallowed

Harmful if inhaled

Causes skin irritation

Causes serious eye irritation

Suspected of causing cancer

Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure  
Flammable liquid and vapor



**Appearance** viscous

**Physical state** liquid

**Odor** Strong Aromatic

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Do not breathe dust/fume/gas/mist/vapors/spray  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Use explosion-proof electrical/ ventilating / lighting/ mixing / equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
Rinse mouth  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Other Information**

Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

#### **Unknown acute toxicity**

0% of the mixture consists of ingredient(s) of unknown toxicity

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS No	Weight-%
Vinyl Ester Resin (non-hazardous) *	Proprietary	30 - 60
Styrene *	100-42-5	10 - 30
Glass, oxide, chemicals *	65997-17-3	10 - 30
Titanium dioxide *	13463-67-7	3 - 7
Barium sulfate *	7727-43-7	3 - 7
Silica, amorphous, precipitated and gel *	112926-00-8	1 - 5

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
<b>Ingestion</b>	Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.
-----------------	---

**Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

#### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO<sub>2</sub>, sand, earth, water spray or regular foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable. Thermal decomposition can lead to release of irritating and toxic gases and vapors.

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** May be ignited by heat, sparks or flames.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Burning produces heavy smoke. Avoid runoff to waterways and sewers.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

**Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

**Incompatible materials** Strong acids. Strong bases. Strong oxidizing agents.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH REL/IDLH
Styrene 100-42-5	STEL: 20 ppm TWA: 10 ppm	TWA: 100 ppm Ceiling: 200 ppm	IDLH: 700 ppm TWA: 50 ppm TWA: 215 mg/m <sup>3</sup> STEL: 100 ppm STEL: 425 mg/m <sup>3</sup>
Glass, oxide, chemicals 65997-17-3	TWA: 1 fiber/cm <sup>3</sup> respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination TWA: 5 mg/m <sup>3</sup> inhalable particulate matter	-	-

Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> CIB 63 ultrafine, including engineered nanoscale
Barium sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Silica, amorphous, precipitated and gel 112926-00-8	-	TWA: 20 mppcf : (80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA	-

NIOSH REL/IDLH Recommended Exposure Limit/Immediately Dangerous to Life or Health

### Appropriate engineering controls

#### Engineering Controls

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin and body protection

Wear protective gloves and protective clothing.

#### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	liquid	Odor	Strong Aromatic
Appearance	viscous	Odor threshold	<1 ppm
Color	pigmented		
<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>	
pH	No information available		
Melting point / freezing point	No information available		
Boiling point / boiling range	115 °C / 239 °F		
Flash point	27 °C / 80 °F	Pensky-Martens Closed Cup (PMCC)	
Evaporation rate	1		
Flammability (solid, gas)	No information available		
Flammability Limit in Air			
Upper flammability limit:	1.1%		
Lower flammability limit:	6.6%		
Vapor pressure	0.57 kPa	@ 20 °C	
Vapor density	>1		
Relative density	1.3		
Water solubility	Insoluble in water		
Solubility in other solvents	No information available		
Partition coefficient	No information available		
Autoignition temperature	No information available		
Decomposition temperature	No information available		
Kinematic viscosity	> 1000 mm <sup>2</sup> /s	@ 40 °C	
Dynamic viscosity	No information available		
Explosive properties	Not an explosive		

**Oxidizing properties** Not applicable

**Other Information**

**Softening point** No information available  
**Molecular weight** No information available  
**VOC Content (%)** No information available  
**Density** No information available  
**Bulk density** No information available

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous polymerization** Hazardous polymerization may occur.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong acids. Strong bases. Strong oxidizing agents.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

**Product Information**

**Inhalation** Irritating to respiratory system. May cause drowsiness or dizziness. Harmful by inhalation.  
**Eye contact** Irritating to eyes.  
**Skin contact** Irritating to skin.  
**Ingestion** Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Styrene 100-42-5	= 1000 mg/kg ( Rat )	-	= 11.7 mg/L ( Rat ) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Barium sulfate 7727-43-7	= 307000 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** Vapors may cause drowsiness and dizziness. Coughing and/ or wheezing. May cause skin irritation. May cause redness and tearing of the eyes.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** Based on available data, the classification criteria are not met.  
**Germ cell mutagenicity** Based on available data, the classification criteria are not met.  
**Carcinogenicity** This product contains titanium dioxide which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is a liquid. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
---------------	-------	------	-----	------

Styrene 100-42-5	A3	Group 2A	Reasonably Anticipated	X
Glass, oxide, chemicals 65997-17-3	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Silica, amorphous, precipitated and gel 112926-00-8	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Group 2A - Probably Carcinogenic to Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

#### Reproductive toxicity

Product is or contains a chemical which is a known or suspected reproductive hazard.

#### STOT - single exposure

Respiratory system. Central nervous system.

#### STOT - repeated exposure

Based on available data, the classification criteria are not met.

#### Chronic toxicity

Avoid repeated exposure. May cause adverse liver effects. Contains a known or suspected reproductive toxin.

#### Target Organ Effects

Central nervous system, Eyes, liver, lungs, Reproductive System, Respiratory system, Skin.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1,139.00 mg/kg

ATEmix (inhalation-dust/mist) 1.95 mg/l

## 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Toxic to aquatic life with long lasting effects

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Styrene 100-42-5	1.4: 72 h Pseudokirchneriella subcapitata mg/L EC50 0.15 - 3.2: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 0.46 - 4.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.72: 96 h Pseudokirchneriella subcapitata mg/L EC50	3.24 - 4.99: 96 h Pimephales promelas mg/L LC50 flow-through 58.75 - 95.32: 96 h Poecilia reticulata mg/L LC50 static 19.03 - 33.53: 96 h Lepomis macrochirus mg/L LC50 static 6.75 - 14.5: 96 h Pimephales promelas mg/L LC50 static	3.3 - 7.4: 48 h Daphnia magna mg/L EC50

#### Persistence and degradability

No information available.

#### Bioaccumulation

Chemical Name	Partition coefficient
Styrene 100-42-5	2.95

#### Other adverse effects

No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

<b>Disposal of wastes</b>	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
<b>Contaminated packaging</b>	Do not reuse container.
<b>US EPA Waste Number</b>	D001

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Styrene 100-42-5	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

<b>UN/ID no</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Special Provisions</b>	B1, B52, IB3, T2, TP1, TP29
<b>Description</b>	UN1263, Paint, 3, III
<b>Emergency Response Guide Number</b>	128

##### TDG

<b>UN/ID no</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>Description</b>	UN1263, Paint, 3, III

##### IATA

<b>UN/ID no</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>ERG Code</b>	3L
<b>Special Provisions</b>	A3, A72, A192
<b>Description</b>	UN1263, Paint, 3, III

##### IMDG

<b>UN/ID no</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>EmS-No</b>	F-E, S-E
<b>Special Provisions</b>	163, 223, 955
<b>Description</b>	UN1263, Paint, 3, III (27°C c.c.); Marine Pollutant

#### 15. REGULATORY INFORMATION

##### International Inventories

<b>TSCA</b>	Complies
<b>DSL/NDL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies



**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Styrene - 100-42-5	0.1
Barium sulfate - 7727-43-7	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Styrene 100-42-5	1000 lb	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Styrene 100-42-5	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Styrene - 100-42-5	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Styrene 100-42-5	X	X	X
Barium sulfate 7727-43-7	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Silica, amorphous, precipitated and gel 112926-00-8	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 2*	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> X
<i>Chronic Hazard Star Legend</i>	<i>* = Chronic Health Hazard</i>			

**Issue Date** 01-Aug-2016

**Revision Date** 03-Apr-2023

**Revision Note**

No information available

**Procedure used to derive the classification**

Justification - Calculation method

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**